

**MOBILE LEADED BARRIER (SHORTY)
WITH 36" x 24" WINDOW**
LB-2436-S, LB-2436-S-ACR

PRODUCT INFORMATION

PHILLIPS-SAFETY.COM

COPYRIGHT ©2025. ALL RIGHTS RESERVED



PHILLIPS SAFETY
PRODUCTS INC.

PRODUCT INFORMATION

MOBILE LEADED BARRIER (SHORTY) WITH 36" x 24" WINDOW

LB-2436-S, LB-2436-S-ACR



The Mobile Leaded Barrier (Shorty) with 36" x 24" Window is a portable, full-body radiation barrier designed to protect against secondary radiation. It features 2.0mm lead equivalent opaque panels of solid, leaded x-ray protection with contoured sides. Its 36" W x 24" H lead equivalency window is a viewing panel which can be chosen in two different materials: a 2.0mm lead equivalent high-quality Schott leaded glass or a 0.5mm lead equivalent leaded acrylic. With an overall size of 39" W x 64" H, this Phillips Safety leaded barrier travels easily on its four-caster locking base steel legs. Please note that the shipping weight is approximately 200 lbs. It is recommended that two people move the barrier together at all times.

SPECIFICATION

WINDOW SIZE: 36" x 24"

PROTECTION: 2.0mm Pb LE opaque panels

WINDOW PROTECTION:

leaded glass 2.0mm Pb LE or acrylic 0.5mm Pb LE

MATERIAL: Lead glass or acrylic, opaque panel solid lead.

FEATURES: Portable, leaded x-ray protection with contoured sides, heavy duty, 4-caster base.

BARRIER AVAILABLE SIZES: 39"W x 64"H

PRODUCT INFORMATION

TILTED MOBILE LEADED BARRIER WITH 24"x30" WINDOW


LB-2430-B, LB-2430-B-ACR

CONTACT

Should you need any further information,
please do not hesitate to contact us.

123 Lincoln Blvd, Middlesex, NJ 08845, USA 

+1 (866) 757 1307 

service@phillips-safety.com 

www.phillips-safety.com 