

SHIELDED WASTE DECAY BARRELS

PRODUCT INFORMATION

PHILLIPS-SAFETY.COM

COPYRIGHT ©2025. ALL RIGHTS RESERVED



PHILLIPS SAFETY
PRODUCTS INC.

PRODUCT INFORMATION
SHIELDED WASTE DECAY BARRELS



The Shielded Waste Decay Barrels can be customized to any size, any thickness of lead shielding, as well as any size or location of drop-port hole. In addition, this Shielded Waste Decay also comes with a lid, which has two heavy-duty handles. Plus, custom designs are also available.

SPECIFICATION

SIZE: Customized

LEAD SHIELDING THICKNESS: Customized

LOCATION OF DROP-PORT HOLE: Customized

COLORS/DESIGN: Customized

FEATURES: Lid, which has two heavy-duty handles


PRODUCT INFORMATION
SHIELDED WASTE DECAY BARRELS

Model Number	Outside Dimensions (In.)	Capacity (gallon)	Lead Shielding (In.)	Lid (In.)	Drop Port Hold (In.)	Finish ⁽⁴⁾	Weight (lbs)
B-5-182430 ⁽¹⁾	18 dia. x 24 h	30	0.50	19 ⁽²⁾ dia.	4.5 dia. ⁽³⁾	P	450
B-5-182430S ⁽¹⁾	18 dia. x 24 h	30	0.50	19 ⁽²⁾ dia.	4.5 dia. ⁽³⁾	SS	450
B-75-182430 ⁽¹⁾	18 dia. x 24 h	30	0.75	19 ⁽²⁾ dia.	4.5 dia. ⁽³⁾	P	600
B-75-182430S ⁽¹⁾	18 dia. x 24 h	30	0.75	19 ⁽²⁾ dia.	4.5 dia. ⁽³⁾	SS	600
B-1-182430 ⁽¹⁾	18 dia. x 24 h	30	1.00	19 ⁽²⁾ dia.	4.5 dia. ⁽³⁾	P	900
B-1-182430S ⁽¹⁾	18 dia. x 24 h	30	1.00	19 ⁽²⁾ dia.	4.5 dia. ⁽³⁾	SS	900
B-1.25-182430 ⁽¹⁾	18 dia. x 24 h	30	1.25	19 ⁽²⁾ dia.	4.5 dia. ⁽³⁾	P	1125
B-1.25-182430S ⁽¹⁾	18 dia. x 24 h	30	1.25	19 ⁽²⁾ dia.	4.5 dia. ⁽³⁾	SS	1125
B-1.5-182430 ⁽¹⁾	18 dia. x 24 h	30	1.50	19 ⁽²⁾ dia.	4.5 dia. ⁽³⁾	P	1350
B-1.5-182430S ⁽¹⁾	18 dia. x 24 h	30	1.50	19 ⁽²⁾ dia.	4.5 dia. ⁽³⁾	SS	1350
B-125-1495S ⁽¹⁾	14 dia. x 9 h	5	0.125	15 ⁽²⁾ dia.	n/a	SS	35
B-25-1495S ⁽¹⁾	14 dia. x 9 h	5	0.25	15 ⁽²⁾ dia.	n/a	SS	55
B-125-141810S ⁽¹⁾	14 dia. x 18 h	10	0.125	15 ⁽²⁾ dia.	n/a	SS	66
B-25-141810S ⁽¹⁾	14 dia. x 18 h	10	0.25	15 ⁽²⁾ dia.	n/a	SS	100
B-125-14.52715 ⁽⁵⁾	14.5 dia. x 27 h	15	0.125	14.5 ⁽⁷⁾ dia.	7 x 7 ⁽⁶⁾	P	95
B-25-14.52715 ⁽⁵⁾	14.5 dia. x 27 h	15	0.25	14.5 ⁽⁸⁾ dia.	7 x 7 ⁽⁶⁾	P	190
B-125-1928.530 ⁽⁵⁾	19 dia. x 28.5 h	30	0.125	19 ⁽⁷⁾ dia.	7 x 7 ⁽⁶⁾	P	145
B-25-1928.530 ⁽⁵⁾	19 dia. x 28.5 h	30	0.25	19 ⁽⁸⁾ dia.	7 x 7 ⁽⁶⁾	P	290
B-125-22.53555 ⁽⁵⁾	22.5 dia. x 35 h	55	0.125	22.5 ⁽⁷⁾ dia.	7 x 7 ⁽⁶⁾	P	200
B-25-22.53555 ⁽⁵⁾	22.5 dia. x 35 h	55	0.25	22.5 ⁽⁸⁾ dia.	7 x 7 ⁽⁶⁾	P	400


(1) Barrel is constructed of rolled sheet lead (2) Lid is constructed of 0.75" thick aluminum-reinforced solid lead with 2 lifting handles. Replacement lids and replacement drop port hole caps are available. (3) Drop port hole can be centered or offset. Drop port hole cap with handle is included. Drop port cap is 0.75" thick lead disk 6" in diameter. (4) P = paint; SS = stainless steel (5) Barrel is a lead-lined steel barrel (6) Drop port hole is centered with a hinged drop port hole cap. (7) Lid has 0.125" lead shielding (8) Lid has 0.25" lead shielding.

CONTACT

Should you need any further information,
please do not hesitate to contact us.

123 Lincoln Blvd, Middlesex, NJ 08846, USA 

+1 866 575 1307 

service@phillips-safety.com 

www.phillips-safety.com 