

LEAD LINED WINDOW FRAME

PRODUCT INFORMATION

PHILLIPS-SAFETY.COM

COPYRIGHT ©2026. ALL RIGHTS RESERVED



PHILLIPS SAFETY
PRODUCTS INC.

PRODUCT INFORMATION
LEAD LINED WINDOW FRAME

LLW-FRAME-1210-1/16 | LLW-FRAME-1212-1/16 | LLW-FRAME-1218-1/16 | LLW-FRAME-2424-1/16 | LLW-FRAME-3048-1/16



The Lead Lined Window Frame provides reliable radiation shielding while seamlessly integrating with your window installation. Crafted from high-quality 16 gauge cold-rolled steel and compliant with ASTM A 366 standards, this frame offers excellent durability and reliability.

Its two-piece telescoping jamb/throat design adjusts from 4-1/8" to 6-1/8", helping accommodate different installation requirements. The frame also features a 2" face profile with a 1/2" return. In addition, 1/16" lead lining provides effective radiation shielding around the window opening.

A gray primer powder finish helps protect the frame against corrosion and wear. The frame also comes with 5/8" glass stops, shipped loose with screws for installation.

The Lead Lined Window Frame is available in five standard sizes:

- 12" x 10"
- 12" x 12"
- 12" x 18"
- 24" x 24"
- 30" x 48"

SPECIFICATIONS

FRAME LEAD LINING: 1/16"	FRAME COLOR/FINISH: Gray Primer Powder Coat
FRAME MATERIAL: 16 Gauge Cold-Rolled Steel	GLASS STOPS: 5/8" (Shipped Loose with Screws)
FRAME TYPE: Two-Piece Telescoping	STANDARD COMPLIANCE: ASTM A 366

CONTACT

Should you need any further information,
please do not hesitate to contact us.

123 Lincoln Blvd, Middlesex, NJ 08846, USA



+1 866 575 1307



service@phillips-safety.com



www.phillips-safety.com

